

SAFE-T-VIEW™ COVER EGRESS WINDOW WELL COVER

SAFE | VIEW COVER

Sloped for drainage

No bracket mounting

Vented design

Clear UV protected polycarbonate over galvanized metal framework
You Can See The Strength™

Compatible with egress ladders

No assembly required

Fits multiple areawall profiles

- Exceeds IRC2003 egress code
- Limited Lifetime Warranty



SV50036 PICTURED

SAFETY RETAINER-HINGE



SQUEEZE-N-SIZE™ ADJUSTABLE MOUNTING



EASY EGRESS



WWW.SAFETVIEWCOVER.COM

St. Paul Consulting Co.
 www.stpaulconsulting.com
 www.safetviewcover.com
 All Rights Reserved
 Safe-T-View Cover is a trademark of St. Paul Consulting Co.
 Made in USA. Patents Pending

Safe-T-View Cover installation instructions

1. Carefully un-wrap your new Safe-T-View Cover without the use of a box cutter (to ensure not damaging the XL polycarbonate). Please contact your local recycling center for responsible disposal of the cardboard packaging.

2. Simply squeeze and size the pre-installed spring clips to the correct length and width dimensions for your previously installed areawall. Hand adjustments can be made as you lay the cover over the window well opening.



3. Attach the safety retainer-hinge lanyards to the top bolts that mount the areawall to the foundation. *Alternatively, anchor the loop end of the lanyard to the home foundation or directly to the areawall itself, depending on your particular application. Allow for enough lanyard length so the cover will pivot up and stay propped open against the side of the house.



4. Peel back the protective film from the UV protected polycarbonate.

Now stand back and take pleasure in the fact that in just minutes, you've installed the sturdiest, most innovative, and easiest to install cover product available today. Well done!

Safe-T-View Limited lifetime warrantee

St Paul Corrugating, ("SPC") warrants Safe-T-View Window Well Covers ("Covers") to the original purchaser for a lifetime against breakage due to defects in materials or workmanship; for a period of ten (10) years from the date of purchase for excessive yellowing or discoloring of the XL polycarbonate, (provided in each case that the Covers are used for their intended purposes only, and are maintained by the purchaser in accordance with the instructions provided with each Cover). Please contact us for the complete details on this unique warranty.

Maintenance & Cleaning

Check cover(s) regularly to see that it has not shifted or moved from its properly installed position. Covers should be kept clean to eliminate the build up of hard water spots. Clean using a non-abrasive cloth with biodegradable soap and water. Hard water deposits can cause discoloration that is not covered under the warranty. Also inspect the cover to see if any parts are broken or missing. Any broken or missing parts should be repaired or replaced immediately. Please contact us for your replacement part needs.